

►► Specification and technical data

MODEL		G50C	G80C	G100C	
PUMP	Type	Self-priming, Centrifugal pump			
	Inlet/Outlet	mm(inch)	50 (2")	80 (3")	100 (4")
	Max.head	(m)	32	28	25
	Suction head	(m)	8	8	8
	Maximum capacity	(L/min)	570	1000	1350
ENGINE	Model	G160F	G200F	G240F	
	Displacement	(cc)	163	196	242
	Maximum output	(KW/3600rpm)	4.1	4.8	5.9
	Fuel tank capacity	(L)	3.6	3.6	6.5
Unit	Dimensions(L x W x H)	(mm)	465 x 370 x 380	512 x 412 x 445	620 x 475 x 575
	Net Weight	(kg)	25	29	47



G50C



G80C



G100C



G80TPC



G80SP



G50HX



G80HX

►► Specification and technical data

MODEL		G80TPC	G80SP	G50HX	G80HX	
PUMP	Type	Trash pump		Self-priming, Centrifugal pump		
	Inlet/Outlet	mm(inch)	80 (3")	80 (3")	50 (2")	80 (3")
	Max.head	(m)	26	27	35	28
	Suction head	(m)	8	8	8	8
	Maximum capacity	(L/min)	1000	1200	540	1000
ENGINE	Model	G200F	G240F	G160F	G200F	
	Displacement	(cc)	196	242	163	196
	Maximum output	(KW/3600rpm)	4.8	5.9	4.1	4.8
	Fuel tank capacity	(L)	3.6	6.5	3.6	3.6
Unit	Dimensions(L x W x H)	(mm)	560 x 440 x 455	660 x 500 x 515	515 x 410 x 400	610 x 410 x 420
	Net Weight	(kg)	38	63	23	25